



System Selection Guide

System	Description	Primary Restrictions	IPEMA Certified	Critical Fall Height	Thickness Ranges	Primary Application	LEED Contribution	Common Substrates	Optional Tops
SpectraPour	2-Layer Poured System EPDM rubber granules (1-4 mm) 20 Standard colors (colors can be mixed)	Install Temps	Yes	4' – 12'	1.75" – 5"	All Uses	3-7 Points	Type 2 Road Base Concrete Asphalt	1-4 mm TPV (lowers LEED)
SpectraPour Supreme	2-Layer Poured System TPV Granules (0.5-1.5 mm) 4 Standard colors other TPV colors available)	Install Temps Limited colors	Yes	4' – 12'	2" – 5"	All Uses	3-6 Points	Type 2 Road Base Concrete Asphalt	
SpectraPour CA	2- or 3-Layer Poured System EPDM rubber granules (1-4 mm) 20 Standard colors (colors can be mixed)	Install Temps	Yes	4' – 12'	1.75" – 5"	CalRecycle TDP Grant Program	3-7 Points	Type 2 Road Base Concrete Asphalt	1-4 mm TPV (lowers LEED)
SpectraTop	1-Layer Poured System SpectraPour Top Layer Only EPDM rubber granules (1-4 mm) 20 Standard colors	Install Temps No Cushion	No	N/A	0.5"	All Uses	3-7 Points	Concrete Asphalt	1-4 mm TPV (lowers LEED)
SpectraBound Tile	24"x24" Factory-Molded Tiles 4 Standard Pigmented Top Colors 20 EPDM Blend Colors 14 UltraTop Blends & Black	Install Temps (better than poured temps)	Yes	6' – 10'	2.5" 3.5" 3.75"	All Uses	3-8 Points	Concrete Asphalt	1-4 mm TPV (lowers LEED)
SpectraTurf PlayGrass	2-Layer Poured System (poured base & turf roll) Green (other colors available)	Install Temps	Yes	4' – 12'	1.75" – 5" (base)	All Uses	3-7 Points	Type 2 Road Base Concrete Asphalt	N/A