

## System Selection Guide

| System                       | Description   | Primary Restrictions                           | IPEMA Certified | Critical Fall Height | Thickness Ranges      | Primary Application                | LEED Contribution | Common Substrates                           | Optional Tops               |
|------------------------------|---|--|-----------------|----------------------|-----------------------|------------------------------------|-------------------|---|-----------------------------|
| <b>SpectraPour</b>           | 2-Layer Poured System<br>EPDM rubber granules (1-4 mm)<br>20 Standard colors<br>(colors can be mixed)                 | Install Temps                                  | Yes             | 4' – 12'             | 1.75" – 5"            | All Uses                           | 3-7 Points        | Type 2 Road Base<br>Concrete<br>Asphalt     | 1-4 mm TPV<br>(lowers LEED) |
| <b>SpectraPour Supreme</b>   | 2-Layer Poured System<br>TPV Granules (0.5-1.5 mm)<br>4 Standard colors<br>other TPV colors available)                | Install Temps<br>Limited colors                | Yes             | 4' – 12'             | 2" – 5"               | All Uses                           | 3-6 Points        | Type 2 Road Base<br>Concrete<br><br>Asphalt |                             |
| <b>SpectraPour CA</b>        | 2- or 3-Layer Poured System<br>EPDM rubber granules (1-4 mm)<br>20 Standard colors<br>(colors can be mixed)           | Install Temps                                  | Yes             | 4' – 12'             | 1.75" – 5"            | CalRecycle<br>TDP Grant<br>Program | 3-7 Points        | Type 2 Road Base<br>Concrete<br>Asphalt     | 1-4 mm TPV<br>(lowers LEED) |
| <b>SpectraTop</b>            | 1-Layer Poured System<br>SpectraPour Top Layer Only<br>EPDM rubber granules (1-4 mm)<br>20 Standard colors            | Install Temps<br>No Cushion                    | No              | N/A                  | 0.5"                  | All Uses                           | 3-7 Points        | Concrete<br>Asphalt                         | 1-4 mm TPV<br>(lowers LEED) |
| <b>SpectraBound Tile</b>     | 24"x24" Factory-Molded Tiles<br>4 Standard Pigmented Top Colors<br>20 EPDM Blend Colors<br>14 UltraTop Blends & Black | Install Temps<br>(better than<br>poured temps) | Yes             | 6' – 10'             | 2.5"<br>3.5"<br>3.75" | All Uses                           | 3-8 Points        | Concrete<br>Asphalt                         | 1-4 mm TPV<br>(lowers LEED) |
| <b>SpectraTurf PlayGrass</b> | 2-Layer Poured System<br>(poured base & turf roll)<br>Green (other colors available)                                  | Install Temps                                  | Yes             | 4' – 12'             | 1.75" – 5" (base)     | All Uses                           | 3-7 Points        | Type 2 Road Base<br>Concrete<br>Asphalt     | N/A                         |